

Anti-Slip Coating

- Makes surfaces non-slip – even when wet
- Does not alter the look of the surface
- UV and water resistant
- Suitable for use on cement, stone and wood



USAGE

Interior and
Exterior

COVERAGE

1 Litre
12 m²

APPLICATION

Brush or
medium haired
roller

DRYING TIME

30 mins to touch
12 hours final

TOOL CLEANING

Water

Product use

Liberon Anti-slip Coating assures a non-slip surface on very smooth and humid interior and exterior flooring. A clear coating, it is suitable for use on cement, concrete, stone, paving and wood. It is ideal for use on smooth and slippery flooring, or in areas of high humidity such as patios, decking, utility rooms and swimming pools.

Preparation

The surface must be clean, dry and have no traces of grease, wax or oil.

Natural surfaces

- Exterior cement / concrete: clean the surface using Liberon Path and Patio Cleaner.
- Decking: clean to remove dirt and dust.
- Tiles: clean and remove all traces of grease.
- Porous surfaces: clean.

Painted surfaces

Remove any flaking paint and clean.

Application

It is essential to stir well before and during each application to ensure the product is evenly mixed. Apply with a brush or medium haired roller. One undiluted coat is normally sufficient; however on very porous surfaces a second coat may be necessary. Allow to dry for 3 hours before applying a second coat and 12 hours before use.

Important: Always test product on a spare surface or inconspicuous area for colour, compatibility and end result.

Cleaning and maintenance

Clean as and when required. In areas of high foot traffic we recommend re-applying one coat once a year, or more if necessary.

Liberon Advice

Ideal conditions for application are between 10° and 25°C when dry.

Packaging

Anti-slip Coating is available in 750 ml and 2.5 L containers.

Health and Safety

Keep out of the reach of children. Do not empty into drains. Use only in well-ventilated areas. Do not allow to freeze.

VOC information

EU limit value for Anti-slip Coating (CatA/E): 150 g/L (2007) / 130 g/L (2010). Anti-slip Coating contains Max 3 g/L VOC.

For further information on this or other Liberon products please contact Liberon Technical Services on 01797 361136.

This document was created with Win2PDF available at <http://www.daneprairie.com>.
The unregistered version of Win2PDF is for evaluation or non-commercial use only.