

## Extreme Varnish

- 8 year guarantee
- Protection against severe weathering: -40°C to +60°C
- For use on exterior woodwork



### USAGE

Exterior

### COVERAGE

1 Litre

12 m<sup>2</sup>

### APPLICATION

Brush or spray

### DRYING TIME

6 hours between coats, 24 hours final

### TOOL CLEANING

White Spirit

### Product use

Liberon Extreme Varnish is a highly protective polyurethane varnish with UV protection which is specially developed to protect against severe weathering (ice, snow...) or prolonged exposure to sunlight. It forms a flexible film which moves with the wood and is resistant to thermal shock. Guaranteed for 8 years it is ideal for use on gates, summer houses and doors, negating the need for annual maintenance.

### Preparation

Bare wood: brush and remove all traces of dust.

Varnished wood: sand thoroughly with fine grade sandpaper (240). If the varnish is flaking remove with Liberon Fine Wood Stripper. Rinse with water and allow to dry for 24 hours. Lightly sand and remove all traces of dust.

### Application

Stir well before use. Apply with a brush or spray, diluting the first coat with up to 10% white spirit. Allow the first coat to dry for 6 hours before applying further coats. We recommend a minimum of 3 coats. For best results gently rub with fine grade sandpaper (240) between coats.

**Important:** Always test product on a spare surface or inconspicuous area for colour, compatibility and end result.

### Precautions

- This product may darken some timbers. A wet surface will be an indication of the final colour.
- Not suitable for use on oak and temperate hardwoods

### Liberon advice

Ideal conditions for application are between 12° and 25°C when dry.

We recommend rounding off the corners of timber work with sand paper to ensure an even coverage of varnish.

### Packaging

Extreme Varnish is available in 750 ml and 2.5 L containers.

### Health and Safety

Flammable. Repeated exposure may cause skin dryness or cracking. Keep out of the reach of children. Do not empty into drains. Use only in well-ventilated areas. If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label. Contains cobalt compound and methylethylketoxime. May produce an allergic reaction.

### VOC information

EU limit value for Extreme Varnish (CatA/E): 500 g/L (2007). Extreme Varnish contains Max 436 g/L VOC.

For further information on this or other Liberon products please contact Liberon Technical Services on 01797 361136.

This document was created with Win2PDF available at <http://www.daneprairie.com>.  
The unregistered version of Win2PDF is for evaluation or non-commercial use only.