



Lubricating Wax

- Lubricates tools and machinery
- Keeps working parts moving freely
- Helps reduce resin build-up from softwood
- Reduces corrosion on all bare metal surfaces
- Silicone free

USAGE

Interior

COVERAGE

1 L
10-12 m²

APPLICATION

Brush or
Cotton Cloth

DRYING TIME

Minimum 10
minutes

TOOL CLEANING

White Spirit

Product use

Liberon Lubricating Wax is specially formulated to lubricate and clean saw blades, cutter blades, machine tables, lathes, planers, veneer presses and G-clamps to increase efficiency and longevity.

Its special properties will inhibit the formation of rust and assist in the quick cleaning and easy removal of glue from veneer presses and G-clamps.

Preparation

Shake well before use. Ensure the surface is clean, dry and free from rust. Remove rust using Liberon Rust Remover.

Application

Apply a thin coat of Lubricating Wax using a brush or clean cotton cloth. Allow to dry before use. Re-apply as required.

Important: Ensure all working machinery is switched off and stationary before using Liberon Lubricating Wax. Allow to dry before switching equipment on.

Maintenance

Use as required to keep tools and machinery in good condition.

Packaging

500 ml, 1 L

For further information on this or other Liberon products please contact Liberon Technical Services on 01797 361136.

This document was created with Win2PDF available at <http://www.daneprairie.com>.
The unregistered version of Win2PDF is for evaluation or non-commercial use only.