

# Path and Patio Sealer

- **Non-colouring, anti-stain and water-proofing treatment for porous stone, brick and concrete**
- **Makes the surface oil resistant**
- **Helps prevent the growth of mould, lichen and moss**
- **Effective after one coat on most surfaces**



#### USAGE

Exterior

#### COVERAGE

1 Litre  
10-12 m<sup>2</sup>\*  
depending upon porosity

#### APPLICATION

Brush

#### DRYING TIME

1 hour to touch  
24 hours final

#### TOOL CLEANING

Water

### Product use

Liberon Path and Patio Sealer is a highly effective sealer that repels water and resists stains, food oils and barbeque marks. It is ideal for use on new or old stone, terracotta, brick, tile and concrete and can also be used on chimineas. The non-colouring formula means there is no change to the look of the stone and it is effective after just one coat on most surfaces.

### Preparation

Ensure the surface is clean and dry. Clean with Liberon Path and Patio Cleaner if required.

### Application

Apply Path and Patio Sealer generously with a paint brush and allow to dry for 24 hours. To check the surface is properly sealed drop a small amount of water onto the surface. Leave for 10-15 minutes and if the water remains on the surface then enough sealer has been applied. If not then further coats of sealer are required.

Repeat application and testing until the surface is properly sealed. The number of coats required will depend upon the porosity of the stone.

**Important:** Always test product on a spare surface or inconspicuous area for colour, compatibility and end result.

### Cleaning and maintenance

Clean with Liberon Path and Patio Cleaner as and when required. Carry out the water drop test once a year and re-apply sealer as necessary.

### Packaging

Path and Patio Sealer is available in 1L and 5 L containers.

### Health and Safety

Keep out of the reach of children. Do not empty into drains. Use only in well-ventilated areas. Do not allow to freeze.

For further information on this or other Liberon products please contact Liberon Technical Services on 01797 361136.

This document was created with Win2PDF available at <http://www.daneprairie.com>.  
The unregistered version of Win2PDF is for evaluation or non-commercial use only.