



Two Part Wood Filler

- Epoxy strength can replace complete sections of wood
- Fast curing
- Shrink and crack resistant
- Suitable for interior and exterior use
- Endorsed by the Guild of Master Craftsmen

USAGE

Interior and exterior

COVERAGE

As required

APPLICATION

Painter's knife

Hardening Time

30 mins

TOOL CLEANING

White Spirit

Product use

Liberon Two Part Wood Filler is made from a mix of wood flour and polyester resin to produce a hardwearing wood substitute. Used to reconstitute missing sections of wood in floors, tables and window frames etc., Liberon Two Part Wood Filler is fast curing and shrink resistant. It can be sanded, nailed and dyed once hardened. The high strength formula is resistant to water and is compatible with most finishing products. Ideal for use prior to painting.

Preparation

Ensure the area to be repaired is clean, dry and free from dust.

Application

Mix a pea size amount of hardener with a soup spoonful of wood filler in the plastic lid. Always work with small quantities as the product hardens very quickly. Immediately place the filler onto the area requiring filling using a Liberon Plastic Scraper or suitable filling knife. Working time of 5- to 10 minutes. The wood filler can be sanded once it has hardened (approximately 30 minutes).

Small holes may be filled in one operation. Bigger areas may be built up in layers.

Important: Two Part Wood Filler will accept dyes/stains differently to surrounding wood.

Packaging

200 g

Colour

Neutral

For further information on this or other Liberon products please contact Liberon Technical Services on 01797 361136.

This document was created with Win2PDF available at <http://www.daneprairie.com>.
The unregistered version of Win2PDF is for evaluation or non-commercial use only.