



Wood Stopping

- **Made from wood pulp**
- **Dries as hard as wood**
- **Ready to use**
- **Quick drying**
- **Easy to sand**
- **Cellulose based solvent**
- **Wide range of colours available**

Product use

Liberon Wood Stopping is a natural wood flour based stopping for filling small holes, cracks and gaps. Wood Stopping is a traditional stopping to make repairs in unfinished wood.

Application

Select the shade of Wood Stopping that most closely resembles the final finished colour required. To obtain other wood shades either mix the Stoppings together or mix in Liberon Earth Pigments before applying.

Spread and press Liberon Wood Stopping into the repair area with a painter's knife or similar tool. For best results resist overspreading, but leave sufficient over fill to enable thorough sanding. Allow to dry thoroughly -10 minutes or longer, depending on the depth of the repair.

Fill deep cavities in several stages, several thin layers will dry more rapidly than one heavy application. Close tin tightly. If contents become dry, this product may be reconstituted with cellulose thinner.

Important: Always test product on a spare surface or inconspicuous area for colour, compatibility and end results. Wood Stopping may accept dyes/stains differently to surrounding wood.

Precautions

- The use of gloves is recommended when applying this product.

Packaging

35 ml, 125 ml, 500 ml

Colours

Neutral, Golden Pine, Antique Pine, Light Oak, Medium Oak, Georgian Mahogany.

For further information on this or other Liberon products please contact Liberon Technical Services on 01797 361136.

This document was created with Win2PDF available at <http://www.daneprairie.com>.
The unregistered version of Win2PDF is for evaluation or non-commercial use only.