

Pre-varnish for wood floors

- · Aids the adhesion and hardening of floor varnish
- · Helps to reduce the darkening of wood when applying a varnish
- · Provides a water resistant coating
- Ideal for old oak and pine
- Recommended for use with Liberon High Resistance Floor Varnish
- Endorsed by the Guild of Master Craftsmen











Product Use

Liberon Pre-varnish gives a long lasting and quality finish to wood and parquet flooring. Recommend for use on sanded floors it reduces the darkening of wood and helps prevent tannins rising to keep the original beauty of the wood when it is varnished. Suitable for use with Liberon High Resistance Floor Varnish, Liberon Pre-varnish reinforces the durability of the varnish and aids application. Pre-varnish is recommended for use on Oak, Pine and most woods.

Preparation

Ensure that the surface is clean and dry. De-wax, sand and remove dust as required.

Application

Shake / stir well before use. The product has a milky appearance which disappears after application. Apply one coat of Pre-varnish evenly using a brush or roller. Allow to dry for a minimum of 1 hour, lightly sanding the surface with a fine sand paper before applying a finish of varnish.

Important: Always test product on a spare surface or inconspicuous area for colour change, compatibility and end result.

Precautions

For use with solvent varnish only. Do not use with oil finishes.

VOC Information

EU limit value for Pre-Varnish (CatA/I): 140 g/L (2007) / 140 g/L (2010). Pre-Varnish contains Max 140 g/L VOC.

Liberon Advice

After sanding and cleaning the floor wipe over with a damp cloth to remove any remaining sawdust. Ideal application conditions are between 12 and 25 °C.

Packaging

750 ml, 2.5 L

For further information on this or other Liberon products please contact Liberon Technical Services on 01797 361136.

This document was created with Win2PDF available at http://www.daneprairie.com. The unregistered version of Win2PDF is for evaluation or non-commercial use only.