

NEW FORMULA:
ODOURLESS

Multi-Purpose Wood Filler



Made from
real wood



Excellent adhesion



Does not shrink



Extremely hard
when dry



Quick drying time



PRODUCT DESCRIPTION

- **Blanchon Multi-Purpose Wood Filler** has been especially designed to fill gaps, cracks and holes in furniture, woodwork or wood floors. Missing parts of furniture (angles, keyholes, etc.) can be made with **Multi-Purpose Wood Filler**.
- **Multi-Purpose Wood Filler** is suitable for all types of work, it is easy to use with excellent adhesion to all wood species.
- It is made from real wood so it behaves just like wood when dry: it can be nailed, screwed, sanded, sawed, painted, stained, varnished, waxed.
- Available in 5 colours: Natural, Light Oak, Medium Oak, Dark Oak, Pine.

SURFACE PREPARATION

- Wood must be clean, dry and free of any existing coatings (varnish, paint, wax, wood floor varnish, etc.).
- It is recommended to degrease new oily exotic woods with acetone before applying **Multi-Purpose Wood Filler**. Traces of resin on softwood (pine, fir, pitch pine, etc.) should also be removed.

DIRECTIONS FOR USE

- **Blanchon Multi-Purpose Wood Filler** is ready to use. If necessary, mix the product before use. Only use in well ventilated areas. Do not leave plants and aquariums in areas where the product is being applied.
- Apply quickly **Multi-Purpose Wood Filler** using a spatula wider than the gap to fill.
- Do not "work" **Multi-Purpose Wood Filler**: it dries very quickly.
- Remove any excess of the filler with a sandpaper, as soon as the product is dry.
- In case the repaired area needs to be stained afterwards, sand carefully around the repaired area to avoid a "halo" effect.
- Fill deep holes in several steps or place pieces of string in the bottom of the hole.
- Reseal the container properly after use.

Cleaning of tools

- Clean tools immediately after use with water. Do not reuse the tin.
- Protecting the environment:
 - Wring out cloths and wipe tools thoroughly after application.
 - Rinse with as little water as possible in a bucket and leave this water to evaporate.
 - The residue may then be disposed of normally in a waste bin.
 - Seal the container properly after use.
 - Dispose of the empty container in a suitable waste collection site.
 - You should ask your local authorities for information about the procedure for disposal and collection.
 - Do not pour the residues down the drain.

DRYING TIME

- Around 30 minutes (for 2mm holes).
- Recoatable as soon as sanding is possible.

STORAGE

- Protect from frost (be careful if stored in vehicles).
- Carefully seal the container after use. Long storage: store the can upside down (lid underneath).

TECHNICAL DATA

USE	FILLING ALL DEFECTS AND GAPS IN MOST WOOD SPECIES
TYPE OF RESINS	Water-based
AFNOR CLASSIFICATION	Family 1, class 7b2
DENSITY	1.15 (at 20°C, as per NF T 30020)
REGULATORY INFORMATION	Refer to the relevant Material Safety Data Sheet (also available on www.blanchon.co.uk or www.quickfds.com)
TYPE OF PRODUCT	Single component product, no mixing required
FLUIDITY	Thick
PIGMENTATION	Colourless

Technical Data Sheet issued on the 20.03.2009. The information provided in this Technical Data Sheet is given in good faith for information purposes only.

In no case whatsoever can this information be considered as a guarantee given by us nor engage our responsibility when our products are used. Since we are constantly striving to improve our products, the information given herein may be subject to modification without prior notice. This Technical Data Sheet cancels and supersedes all previous versions.

28, rue Charles Martin - BP 105
69192 SAINT-FONS CEDEX - FRANCE
Tél. 04 72 89 06 00 - Fax 04 78 70 07 18
Export Lines: Tel. (0033) 472 89 06 09
Fax (0033) 472 89 06 02

Blanchon

BLANCHON S.A. - Est. 1832 - A stock company with a board of directors and a supervisory board, with a registered capital of € 4 258 258 - 390 112 886 RCS LYON - APE 2030 Z - E-mail: info.uk@blanchon.com - Internet: www.blanchon.co.uk