

# impralan<sup>®</sup>-End-grain Sealer

**Water-borne sealer protecting end-grain surfaces against humidity.**

|   |  |
|---|--|
| <b>Fields of application</b>            | Colourless sealer protection end-grain surfaces against humidity.  |
| <b>Characteristics</b>                  | <ul style="list-style-type: none"> <li>• Reliable prevention of humidity absorption</li> <li>• Quick-drying</li> <li>• Easy to apply</li> <li>• Good adhesion of following impralan<sup>®</sup> coatings</li> <li>• Density approx. 1.0 g/cm<sup>3</sup> at 20°C.</li> </ul> |
| <b>Composition</b>                      | Acrylate dispersion, water, glycols, additives, preserving agents.   |
| <b>Colour</b>                           | 0000-colourless.   |
| <b>Pack size</b>                        | 0,25 litres, 0.75 litre and 2.5 litres.  |
| <b>Application method</b>               | Brushing   |
| <b>Application rate</b>                 | Approx. 200-400 ml/m <sup>2</sup> depending on absorption capacity of surface.   |
| <b>Application recommendations</b>      | Before glueing apply protective sealer with brush with short bristles. Only apply on end-grain surfaces. If applied on other surfaces discolorations may occur. Do not apply and dry at temperatures of less than +10°C (product, surface and air)                           |
| <b>Drying time</b>                      | Under normal conditions (65% relative air humidity / 20°C) can be re-coated after approx. 4 hours.<br>High air humidity and low temperatures delay drying.   |
| <b>Cleaning tools</b>                   | Rinse with water immediately after use.  |
| <b>Regulation on hazardous material</b> | The product is not subject to specific labelling under current EU regulations.   |
| <b>Precautions</b>                      | When working with wood preservatives always observe the safety precautions for handling and personal safety. Material Safety Data Sheet available for professionals upon demand.   |
| <b>Storage/ Transport</b>               | Cool, but not exposed to frost, can be stored for at least 1 year. Reseal opened containers tightly after use. Keep only in the original container, to be handled by competent persons.<br>RID/ADR: Not restricted.  |

|  |   |
|--|---|
| <b>Environmental protection</b>  | Do not allow impralan®-End-grain Sealer to seep into the soil, water or drainage channels. European waste catalogue no. 08 01 12. |
| <p>This technical leaflet has been compiled to the best of our knowledge and experience. In view of the large number of applications, we are unable to give a guarantee for every case. In cases of doubt, our technical department should be contacted for further advice.</p> <p>Verbal agreements and assurances warrant written confirmation.</p> <p>This technical leaflet supersedes all preceding ones.</p> |   |

604015GB/ 2010-02-03