

A G WOODCARE PRODUCTS LTD

Unit 3, Wellington Road, Waterloo Ind Est, Bidford-on-avon, B50 4JJH

Telephone: 01789 778628 / Fax 01789 490296

Email - email@agwoodcare.co.uk

WWW.AGWOODCARE.CO.UK

HARD WAX OIL

A blend of natural oils & waxes offering exceptional durability & resistance for internal natural wood flooring, kitchen worktops (wood) and areas subjected to a high degree of wear.

Produces a quick drying, natural satin / matt water repellent, tread-fast finish that will not peel or flake. To maintain / renovate, simply wash, buff or re-apply, following the guidelines below.

Suitable for application onto children's toys – EN 71-Toy Safety Certification

Resistant to liquids: Tested in accordance with BS 3900 G5

Resistant to wear: Tested in accordance with BS3900 E15



PREPARATION

Ensure all surfaces are clean, dry, and free from any previous finish. Sand the substrate with a fine 150 grade sanding paper or 150 grit sanding disk, removing all traces of dust.

APPLICATION

Ensure all areas to be coated are extremely well ventilated during and after application. Always test on a small area prior to initial application. No primer required. Maximum 2 coats recommended. Apply at room temperature. Fiddes Hard Wax Oil is formulated for application directly, and does not require thinning.

First Coat - Stir contents thoroughly before and during use, and apply in a warm, well ventilated room. Apply **THINLY** using Fiddes Floor Oil Brush or a good quality bristle or synthetic brush, and lay **EVENLY**, following the direction of the grain. Remove any surplus material immediately with a cloth, carefully checking all areas for any excess application. Leave to dry 4-6 hours in warm, dry well ventilated conditions, or preferably overnight.

Second Coat - Apply as first coat, **THINLY**, allowing good ventilation. Leave to dry 4-6 hours in warm, dry well ventilated conditions, or preferably overnight. Clean applicator with White Spirit. When the surface area is completely dry, a light buff will further enhance the sheen level.

NOTES

Ensure all areas to be coated are extremely well ventilated during and after application has occurred. Always test on small area prior to major application. Clean applicators with White Spirit. Certain dense or oily substrates may only require a single application, and subsequently buffed to achieve the desired finish.

Longer drying periods may occur during application in cold, damp or humid conditions.

Always apply sparingly and remove any excess product thoroughly.

Re-Application: To renovate previous application of Fiddes Hard Wax Oil, lightly sand area with 150 grit sandpaper, and re-apply sparingly.

Coverage: A single application will cover approximately 20-24 square meters per litre, depending on the density of the substrate.

Packaging: 2.5lt