

A G WOODCARE PRODUCTS LTD

Unit 3, Wellington Road, Waterloo Ind Est, Bidford-on-avon, B50 4JJH

Telephone: 01789 778628 / Fax 01789 490296

Email - email@agwoodcare.co.uk

WWW.AGWOODCARE.CO.UK

SUPREME LIMING WAX

Formulated to offer a white shade to stained or bare wood, Fiddes Supreme Liming Wax produces a traditional 'Limed' finish, normally associated with period oak furniture. Fiddes Liming Wax is ideal for application on woods such as oak, or those which normally exhibit distinctive deep grain pattern.

On application, Fiddes Liming Wax fills the open wood pores, offering contrasting white tone and emphasizing the grain across the whole surface area, typical of a traditional 'Limed' finish.

PREPARATION

Sand the wooden substrate in stages, working with a medium sandpaper (120 grit), through to a medium / fine grade (180 –220 grit). Always sand in the direction of the grain pattern where possible, ensuring the removal of any blemishes and glue residue prior to the application of Fiddes Supreme Liming Wax.

Take a clean wire brush and drag along the grain to open pores and emphasize grain pattern. Seal with a coat of Transparent Shellac Polish.

APPLICATION

Apply liberally with a lint free cotton cloth or 0000 steel wool, working well into the grain in a circular motion. Once the surface is completely covered, rub lightly across the grain making sure the liming wax remains in the open pores. Leave approximately 5-10 minutes and buff in the direction of the grain with a soft cotton cloth. Finish with a coat of Clear Supreme Wax Polish to further enhance sheen level and protection.

Application: Cloth, Brush, Sponge.

Dry Time: 3 minutes at room temperature.

Coverage: 16 sqm per Litre (depending on substrate and method of application)

Coats: 1 coat – further coats will deepen colour / shade and enhance sheen level.

Recommended for use on: Fine Furniture, Doors, Floors, Cabinet Work and Panelling.

Packaging: 5lt Containers.

