the perfect finish

ISF SAFETY DATA SHEET 44

Thurmaston Boulevard Leicester LE4 9HS United Kingdom Tel: 0116 274 2222 Fax: 0116 274 3333

www.isf.co.uk

RELEASED

ISSUE No.

IDENTIFICATION PCT-9-TH020-025

FLAMMABLE.

PCT Anti-Bloom Retarding Thinners

22/11/2009

MM07

INGREDIENT NAME

COMPOSITION/INFORMATION ON INGREDIENT | (*) Denotes - See OTHER INFORMATION

TWA (8hr) PPM

TWA (15mins) PPM

0.880

R PHRASES

BUTYL ACETATE

CONC %

90-100

150

200

10

HAZARD IDENTIFICATION

FIRST AID MEASURES

EYES:

FLUSH WITH WATER FOR 10 MINUTES, GET MEDICAL AID.

SKIN:

WASH WITH SOAP & WATER, LAUNDER SOAKED CLOTHING BEFORE RE-USE.

INHALATION:

REMOVE TO FRESH AIR. GET MEDICAL AID IF UNCONSCIOUS TURN TO RECOVERY POSITION.

INGESTION:

DO NOT INDUCE VOMITING, GET MEDICAL AID. IF PATIENT VOMITS TURN TO RECOVERY POSITION.

FIRE FIGHTING MEASURES

USE CARBON DIOXIDE, DRY CHEMICAL, SAND OR EARTH, USE WATER FOG TO COOL SURFACES.

ACCIDENTAL RELEASE MEASURES

ELIMINATE SOURCES OF IGNITION. AVOID INHALING VAPOUR. EVACUATE PERSONNEL. ABSORB LIQUID WITH NON COMBUSTIBLE MATERIAL. IF PRODUCT HAS ENTERED DRAINS INFORM FIRE BRIGADE.

HANDLING AND STORAGE

USAGE PRECAUTIONS: USE IN A FLAME PROOF AREA. FURTHER INSTRUCTIONS ON CONTAINER OR DATA SHEET.

STORAGE PRECAUTIONS: KEEP CONTAINER CLOSED. STORE IN A COOL DRY WELL VENTILATED AREA AWAY FROM

SOURCES OF IGNITION.NO SMOKING.

PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE:

LOW VISCOSITY CLEAR LIQUID.

FLASHPOINT (C):

23

BOILING POINT (C)

126

EVAPORATION RATE:

100

EXPLOSIVE LIMIT

1.7 to 15%

SPECIFIC GRAVITY

0.88

SOLUBILITY @ 20 CELCIU

0.79%

ISF SAFETY DATA SHEET 44

PAGE 1 OF 2

EXPOSURE CONTROLS AND PERSONAL PROTECTION

RESPIRATORY:

AVOID INHALING VAPOUR USE WITH CONTROLLED EXTRACTION AND/OR APPROVED FACE MASK

USE IMPERVIOUS GLOVES & OVERALLS

SKIN

EYES:

IF THERE IS RISK TO EYES USE APPROVED SAFETY GLASSES OR GOGGLES

STABILITY AND REACTIVITY

STABLE UNDER NORMAL STORAGE CONDITIONS

TOXICOLOGICAL INFORMATION

SKIN TOXICITY:

CHRONIC SKIN CONTACT MAY CAUSE DERMATITIS.

EYE TOXICITY:

IRRITATING TO EYES.

INHALED TOXICITY: MAY CAUSE DROWSINESS, NAUSEA, DIZZINESS.

INGESTED

MAY CAUSE VOMITING, IRRITATION OF DIGESTIVE TRACT.

TOXICITY:

ECOLOGICAL INFORMATION

UNLIKELY TO BIOACCUMULATE.

DISPOSAL CONSIDERATIONS

LAND FILL OR INCINERATE IN ACCORDANCE WITH LOCAL REGULATIONS USING AUTHORISED PERSONNEL.

TRANSPORT INFORMATION

UN NUMBER:

1263

PROPER SHIPPING NAME:

PAINT

IMDG CLASS:

3.3

MARINE POLLUTANT:

PACKING GROUP

111

ADR/RID:

REGULATORY INFORMATION

LABEL SYMBOLS





RISK PHRASES: R10. FLAMMABLE.UN 1263 PAINT RELATED PRODUCT

SAFETY PHRASES: S7 KEEP CONTAINER TIGHTLY CLOSED. S16.KEEP AWAY FROM SOURCES OF IGNITION. NO SMOKING.

OTHER INFORMATION

Every effort has been made to keep the information contained on this document as accurate as possible. However the company cannot be held responsible for any errors contained within

* TWA EH40/2002. This information is based on our present state of knowledge. It should not therefore be construed as guaranteeing specific properties of the products described or their suitability for a particular application.