



ISF SAFETY DATA SHEET 48

ISF Group Ltd
Thurmaston Boulevard Leicester
LE4 9HS United Kingdom
Tel: 0116 274 2222 Fax: 0116 274 3333
www.isf.co.uk

IDENTIFICATION	PC2-4-SE010-025	PC2 (Melamine) Clear Sanding Sealer	RELEASED	ISSUE No.
			08/03/2009	MM09

COMPOSITION/INFORMATION ON INGREDIENT	(*) Denotes - See OTHER INFORMATION	VOC	0.630
--	-------------------------------------	-----	-------

INGREDIENT NAME	CONC %	TWA (8hr) PPM	TWA (15mins) PPM	R PHRASES
ISO PROPANOL.	10-15	400	500	F11
TOLUENE	20-25	50	150 SK	F11. Xn20
XYLENE	8-12	100	150 SK	10. Xn 20/21 Xi 38.
METHYL ETHYL KETONE	12-16	200	300 SK	F11 Xi 36/37.
BUTYL ACETATE	12-18	150	200	10

HAZARD IDENTIFICATION	HIGHLY FLAMMABLE. EXPLOSIVE VAPOUR IRRITATING TO RESPIRATORY SYSTEM.
------------------------------	--

FIRST AID MEASURES

EYES:	WASH WITH WATER
SKIN:	WASH SKIN WITH SOAP & WATER
INHALATION:	REMOVE TO FRESH AIR.GET MEDICAL AID. IF UNCONSCIOUS TURN TO RECOVERY POSITION.
INGESTION:	DO NOT INDUCE VOMITING. GET MEDICAL AID. IF PATIENT VOMITS TURN TO RECOVERY POSITION.

FIRE FIGHTING MEASURES

USE CARBON DIOXIDE, DRY CHEMICAL, SAND OR EARTH. USE WATER FOG TO COOL SURFACES.

ACCIDENTAL RELEASE MEASURES

ELIMINATE SOURCES OF IGNITION. AVOID INHALING VAPOUR. EVACUATE PERSONNEL. ABSORB LIQUID WITH NON COMBUSTIBLE MATERIAL. IF PRODUCT HAS ENTERED DRAINS INFORM FIRE BRIGADE.

HANDLING AND STORAGE

USAGE PRECAUTIONS:	USE IN A FLAME PROOF AREA. FURTHER INSTRUCTIONS ON CONTAINER OR DATA SHEET.
STORAGE PRECAUTIONS:	KEEP CONTAINER CLOSED. STORE IN A COOL DRY WELL VENTILATED AREA AWAY FROM SOURCES OF IGNITION. NO SMOKING.

PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE:	LOW VISCOSITY CLEAR LIQUID.		
FLASHPOINT (C):	-4	BOILING POINT (C)	79
EVAPORATION RATE:		EXPLOSIVE LIMIT	
SPECIFIC GRAVITY	1.22	SOLUBILITY @ 20 CELCIU	

EXPOSURE CONTROLS AND PERSONAL PROTECTION

RESPIRATORY: AVOID INHALING VAPOUR. USE WITH CONTROLLED EXTRACTION AND/OR APPROVED FACE MASK.

SKIN: USE IMPERVIOUS GLOVES & OVERALLS.

EYES: IF THERE IS A RISK TO EYES , USE APPROVED GLASSES OR GOGGLES.

STABILITY AND REACTIVITY

STABLE UNDER NORMAL STORAGE CONDITIONS

TOXICOLOGICAL INFORMATION

SKIN TOXICITY: IRRITATING TO SKIN.MAY BE ABSORBED. CHRONIC SKIN CONTACT MAY CAUSE DERMATITIS.

EYE TOXICITY: IRRITATING TO EYES.

INHALED TOXICITY: MAY CAUSE DROWSINESS, NAUSEA, DIZZINESS.

INGESTED TOXICITY: MAY CAUSE VOMITING, IRRITATION OF DIGESTIVE TRACT.

ECOLOGICAL INFORMATION

UNLIKELY TO BIOACCUMULATE. LOW TOXICITY TO FISH.

DISPOSAL CONSIDERATIONS

LAND FILL IN ACCORDANCE WITH LOCAL REGULATIONS USING AUTHORISED PERSONNEL.

TRANSPORT INFORMATION

UN NUMBER:	1263	PROPER SHIPPING NAME:	PAINT
IMDG CLASS:	3.2	MARINE POLLUTANT:	NO
PACKING GROUP	11	ADR/RID:	33.

REGULATORY INFORMATION

LABEL SYMBOLS



RISK PHRASES:

R11. R 20/21.

SAFETY PHRASES:

S7. S9. S16. S25. AVOID SKIN AND EYE CONTACT. S29. DO NOT EMPTY INTO DRAINS. S33. TAKE PRECAUTIONS AGAINST STATIC DISCHARGE.UN 1263 PAINT RELATED PRODUCT

OTHER INFORMATION

Every effort has been made to keep the information contained on this document as accurate as possible. However the company cannot be held responsible for any errors contained within

* TWA EH40/2002. This information is based on our present state of knowledge. It should not therefore be construed as guaranteeing specific properties of the products described or their suitability for a particular application.