

Natural Finish Stone Floor Sealer

- **Non-colouring, maintains the natural look of the stone**
- **Water proofs and protects from staining**
- **Effective after just one coat on most surfaces**



USAGE

Interior

COVERAGE

1 L ml

10-12 m²

APPLICATION

Brush

DRYING TIME

1h to touch
24h final

TOOL CLEANING

Water

Product use

Liberon Natural Finish Stone Floor Sealer is a highly effective sealer for protecting interior terracotta, slate, York stone, ceramic, marble and many similar types of porous stone flooring. A water based product, Liberon Natural Finish Stone Floor Sealer makes the surface resistant to water, stains, food oils and grease marks. Ideal for use on new or old stone it is effective after just one coat on most surfaces.

Preparation

Ensure the surface is clean and dry. If necessary clean with Liberon Stone Floor Cleaner, rinse and allow to dry thoroughly before applying Stone Floor Sealer.

Application

Apply Stone Floor Sealer generously with a paint brush and allow to dry for one hour. Check if the surface is properly sealed by dropping a small amount of water onto the surface. Leave for 10-15 minutes and if the water remains on the surface then enough sealer has been applied. If not then further coats of sealer are required. Repeat application and testing until the surface is properly sealed. The number of coats required will depend upon the porosity of the stone.

Allow the final coat of sealer to dry for 24 hours before use. If required, finish with either Liberon Stone Floor Wax or Liberon Stone Floor Shine for a more durable surface.

Important: Always test product on a spare surface or inconspicuous area for colour, compatibility and end result.

Cleaning and maintenance

Clean with Liberon Stone Floor Cleaner as and when required. Carry out the water drop test once a year and re-apply sealer as necessary.

Precautions

Not suitable for use on oiled surfaces. For previously oiled surfaces, use Liberon Stone Floor Sealer.

Health and Safety

Keep out of the reach of children. Do not empty into drains. Use only in well-ventilated areas. Do not allow to freeze.

Packaging

Liberon Pre-varnish is available in 1 L and 5 L containers.

This product should be used in accordance with the manufacturer's instructions. Recommendations are for guidance only since conditions of use are completely beyond our control. For technical or practical information on this or other Liberon products please contact Liberon on 01797 367555.

Liberon Limited, Mountfield Industrial Estate, New Romney, Kent TN28 8XU. Tel: 01797 367555 Fax: 01797 367575 www.liberon.co.uk
Liberon Ltd is a V33 Group Company.