

Ring Remover

- Removes most white water and heat marks
- Suitable for use on varnishes, lacquers and French polishes
- Revives and shines most finishes
- Safe to use on Teak
- Non-colouring



Product use

Liberon Ring Remover removes most white water marks and heat marks from highly polished surfaces, including French polishes, lacquers, varnishes and modern hard finishes.

Application

Shake well before use. Apply using a clean, lint-free cotton cloth and rub vigorously over the mark, going with the grain, until it is removed. Buff with a clean, dry cotton cloth then wax or polish as normal. For badly marked surfaces, Ring Remover may be applied using Ultra Fine Steel Wool (grade 0000) and then buffed with a cotton cloth.

Important: Always test products first on an inconspicuous area for colour, compatibility and end result.

Coverage

Depends on use.

Tool cleaning

White spirit

Precautions

- Ring Remover may produce a shiny surface when used on matt or satin finishes. If this occurs gently matt back the surface with Liberon Ultra Fine Steel Wool (0000) and re-wax with Liberon Furniture Wax.
- White marks made by water or heat on waxed surfaces may be removed using Liberon Wax and Polish Remover.
- Dark marks made by water or heat indicate damage to the wood. The finish may need to be completely removed so the bare wood can be treated with Liberon Wood Bleacher.

Heath and Safety

Harmful: contains aliphatic solvents. Flammable. Harmful: May cause lung damage if swallowed. Repeated exposure may cause skin dryness or cracking. Keep out of reach of children. Do not empty into drains. Use only in well ventilated areas. If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

Risk of self-combustion for cloths or tools coated in the product. Dispose in an air-tight metal container.

Contains 30% or more aliphatic hydrocarbons. Contains perfume.

Packaging

Burnishing Cream is available in 125ml.

This product should be used in accordance with the manufacturer's instructions. Recommendations are for guidance only since conditions of use are completely beyond our control. For technical or practical information on this or other Liberon products please contact Liberon Technical Services on 01797 367555

Liberon Limited, Mountfield Industrial Estate, New Romney, Kent TN28 8XU.
Tel: 01797 367555 Fax: 01797 367575 www.liberon.co.uk
Liberon Ltd is a V33 Group Company