



PARAMOSE®

How to use: page 1

PARAMOSE PAINT VARNISH REMOVER (ORIGINAL)

- Cover top with a cloth during opening to avoid splashes.
- Apply generous, even coat with a suitable brush (never spread too thin).
- Leave until surface coating reacts (approximately 5-30 minutes) depending on type of coating.
- Once surface has blistered apply a second generous coat onto the blistered paint or varnish and leave to penetrate down to the substrate.
- Scrape off leaving surface as clean as possible following wood grain at all times.
- Apply a third coat onto any stubborn areas and leave for 5 minutes.
- Following wood grain rub down with coarse wire wool (grade 3) until surface is clean and dry.

To be used on

- Any wood or architectural furniture.
- Metal.
- Glass.
- Ceramics.
- Wood veneers.

Who uses Paramose

- Antique restoration and refurbishment companies.
- Paint lacquer distributors.
- DIY.
- Paint merchants.
- Industrial applications.

Preparation

- Ensure surfaces to be stripped are dry.
- Protection should be provided for floor coatings, or any surface that may be damaged by Paramose (perspex, plastics, rubber etc).



PARAMOSE®

How to use: page 2

PARAMOSE PAINT VARNISH REMOVER (ORIGINAL)

Key Notes

- Health and safety data sheets to be consulted.
- Suitable gloves, goggles and protective clothing should be worn.
- Paramose must be shaken well before use.
- Always apply generous, even coats.
- Do not try to spread the product too far, as this will result in poor penetration and faster evaporation.
- Allow Paramose to do its work, do not try to remove too quickly.
- Never let the surface become too dry during treatment.

Difficult Areas

- Paramose paint and varnish remover (thin) is a very versatile product.
- It will outperform a gel type stripper 90% of the time.
- Even though Paramose paint varnish remover is a thin product, when applied correctly it is far less messy than a gel stripper and usage is much lower.
- Applying the second coat of stripper onto the first coat reduces the evaporation rate dramatically and allows the product to penetrate much deeper, eliminating the need for the multi-scrape scenario that is associated with other products.

Benefits with using Paramose Paint & Varnish Remover (Original)

- Thinner consistency, so less product is used.
- Low evaporation.
- Less scraping required.
- Faster and easier to apply.