

# SAFETY DATA SHEET

(REACH regulation (EC) n° 1907/2006 - n° 453/2010)

## SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

### 1.1. Product identifier

Product name : S.O. PRIMER

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

### 1.3. Details of the supplier of the safety data sheet

Registered company name : BLANCHON .

Address : 28, rue Charles Martin B.P. 105.69190.SAINT FONS.FRANCE.

Telephone : 00.33.4.72.89.06.09. Fax : 00.33.4.72.89.06.02.

fds@blanchon.com

### 1.4. Emergency telephone number : 00.33.1.45.42.59.59.

## SECTION 2 : HAZARDS IDENTIFICATION

### 2.1. Classification of the substance or mixture

In compliance with EC regulation No. 1272/2008 and its amendments.

Flammable liquid, Category 2 (Flam. Liq. 2, H225).

Eye irritation, Category 2 (Eye Irrit. 2, H319).

This mixture does not present an environmental hazard. No known or foreseeable environmental damage under standard conditions of use.

In compliance with directives 67/548/EEC, 1999/45/EC and their amendments.

Highly flammable (F, R 11).

Eye irritation (Xi, R 36).

This mixture does not present an environmental hazard. No known or foreseeable environmental damage under standard conditions of use.

### 2.2. Label elements

In compliance with EC regulation No. 1272/2008 and its amendments.

Hazard pictograms :



Signal Word :

DANGER

Hazard statements :

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

Precautionary statements - Prevention :

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ventilating/lighting/.../equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P264 Wash ... thoroughly after handling.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

This Safety Data Sheet is prepared in accordance with  
Annex II to Regulation (EC) No 1907/2006

First editing date : 10/09/1997  
Date of last updating : 24/04/2012  
Validation date : 27/03/2014

## Precautionary statements - Response :

P303 + P361 + P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337 + P313 If eye irritation persists: Get medical advice/attention.

P370 + P378 In case of fire: Use ... for extinction.

## Precautionary statements - Storage :

P403 + P235 Store in a well-ventilated place. Keep cool.

## Precautionary statements - Disposal :

P501 Dispose of contents / container to an approved landfill.

## 2.3. Other hazards

The mixture does not contain any substances classified as 'Substances of Very High Concern' (SVHC) by the European Chemicals Agency (ECHA) under article 57 of REACH: <http://echa.europa.eu/fr/candidate-list-table>

The mixture satisfies neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

## SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS

## 3.2. Mixtures

## Composition :

Identification	(EC) 1272/2008	67/548/EEC	Note	%
CAS: 64-17-5 EC: 200-578-6 REACH: 01-2119457610-43 ETHANOL	GHS07, GHS02 Dgr Flam. Liq. 2, H225 Eye Irrit. 2, H319	Xi,F Xi;R36 F;R11	[1]	50 <= x % < 100
INDEX: 603-117-00-0 CAS: 67-63-0 EC: 200-661-7 REACH: 01-2119457558-25 PROPAN-2-OL	GHS02, GHS07 Dgr Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336	Xi,F Xi;R36 F;R11 R67	[1]	2.5 <= x % < 10
INDEX: 606-002-00-3 CAS: 78-93-3 EC: 201-159-0 REACH: 01-2119457290-43 BUTANONE	GHS02, GHS07 Dgr Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 EUH:066	Xi,F Xi;R36 F;R11 R66-R67	[1]	2.5 <= x % < 10
CAS: 123-42-2 EC: 204-626-7 REACH: 01-2119473975-21 DIACETONE ALCOHOL	GHS07, GHS02 Wng Flam. Liq. 3, H226 Eye Irrit. 2, H319 STOT SE 3, H335	Xi Xi;R36/37	[1]	2.5 <= x % < 10

## Information on ingredients :

[1] Substance for which maximum workplace exposure limits are available.

## SECTION 4 : FIRST AID MEASURES

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing by an unconscious person.

## 4.1. Description of first aid measures

## In the event of splashes or contact with eyes :

Wash thoroughly with soft, clean water for 15 minutes holding the eyelids open.

If there is any redness, pain or visual impairment, consult an ophthalmologist.

## In the event of swallowing :

In the event of swallowing, if the quantity is small (no more than one mouthful), rinse the mouth with water and consult a doctor.

Keep the person exposed at rest. Do not force vomiting.

Seek medical attention, showing the label.

If swallowed accidentally, call a doctor to ascertain whether observation and hospital care will be necessary. Show the label.

This Safety Data Sheet is prepared in accordance with  
Annex II to Regulation (EC) No 1907/2006

First editing date : 10/09/1997  
Date of last updating : 24/04/2012  
Validation date : 27/03/2014

**4.2. Most important symptoms and effects, both acute and delayed**

No data available.

**4.3. Indication of any immediate medical attention and special treatment needed**

No data available.

---

**SECTION 5 : FIREFIGHTING MEASURES**

Flammable.

Chemical powders, carbon dioxide and other extinguishing gas are suitable for small fires.

**5.1. Extinguishing media**

Keep packages near the fire cool, to prevent pressurised containers from bursting.

**Suitable methods of extinction**

In the event of a fire, use :

- sprayed water or water mist
- water with AFFF (Aqueous Film Forming Foam) additive
- halon
- foam
- multipurpose ABC powder
- BC powder
- carbon dioxide (CO<sub>2</sub>)

Prevent the effluent of fire-fighting measures from entering drains or waterways.

**Unsuitable methods of extinction**

In the event of a fire, do not use :

- water jet

**5.2. Special hazards arising from the substance or mixture**

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed :

- carbon monoxide (CO)
- carbon dioxide (CO<sub>2</sub>)

**5.3. Advice for firefighters**

Fire-fighting personnel are to be equipped with autonomous insulating breathing apparatus.

---

**SECTION 6 : ACCIDENTAL RELEASE MEASURES****6.1. Personal precautions, protective equipment and emergency procedures**

Consult the safety measures listed under headings 7 and 8.

**For non first aid worker**

Because of the organic solvents contained in the mixture, eliminate sources of ignition and ventilate the area.

Avoid any contact with the skin and eyes.

**For first aid worker**

First aid workers will be equipped with suitable personal protective equipment (See section 8).

**6.2. Environmental precautions**

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

**6.3. Methods and material for containment and cleaning up**

Clean preferably with a detergent, do not use solvents.

**6.4. Reference to other sections**

No data available.

---

**SECTION 7 : HANDLING AND STORAGE**

Requirements relating to storage premises apply to all facilities where the mixture is handled.

**7.1. Precautions for safe handling**

Always wash hands after handling.

Remove and wash contaminated clothing before re-using.

Ensure that there is adequate ventilation, especially in confined areas.

This Safety Data Sheet is prepared in accordance with  
Annex II to Regulation (EC) No 1907/2006

First editing date : 10/09/1997  
Date of last updating : 24/04/2012  
Validation date : 27/03/2014

**Fire prevention :**

Handle in well-ventilated areas.

Vapours are heavier than air. They can spread along the ground and form mixtures that are explosive with air.

Prevent the formation of flammable or explosive concentrations in air and avoid vapor concentrations higher than the occupational exposure limits.

Prevent the accumulation of electrostatic charges with connections to earth.

The mixture can become electrostatically charged : always earth during decanting operations. Wear antistatic shoes and clothing and floors should be electrically conductive.

Use the mixture in premises free of naked flames or other sources of ignition and ensure that electrical equipment is suitably protected.

Keep packages tightly closed and away from sources of heat, sparks and naked flames.

Do not use tools which may produce sparks. Do not smoke.

Prevent access by unauthorised personnel.

**Recommended equipment and procedures :**

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

Avoid eye contact with this mixture.

Packages which have been opened must be reclosed carefully and stored in an upright position.

**Prohibited equipment and procedures :**

No smoking, eating or drinking in areas where the mixture is used.

**7.2. Conditions for safe storage, including any incompatibilities**

No data available.

**Storage**

Keep the container tightly closed in a dry, well-ventilated place.

Keep away from all sources of ignition - do not smoke.

Keep well away from all sources of ignition, heat and direct sunlight.

Avoid accumulation of electrostatic charges.

The floor must be impermeable and form a collecting basin so that, in the event of an accidental spillage, the liquid cannot spread beyond this area.

**Packaging**

Always keep in packaging made of an identical material to the original.

**7.3. Specific end use(s)**

No data available.

---

**SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION****8.1. Control parameters****Occupational exposure limits :**

- European Union (2009/161/EU, 2006/15/EC, 2000/39/EC, 98/24/EC)

CAS	VME-mg/m <sup>3</sup> :	VME-ppm :	VLE-mg/m <sup>3</sup> :	VLE-ppm :	Notes :
78-93-3	600	200	900	300	-

- France (INRS - ED984 :2008) :

CAS	VME-ppm :	VME-mg/m <sup>3</sup> :	VLE-ppm :	VLE-mg/m <sup>3</sup> :	Notes :	TMP No :
64-17-5	1000	1900	5000	9500	-	84
67-63-0	-	-	400	980	-	84
78-93-3	200	600	300	900	*	84
123-42-2	50	240	-	-	-	84

- UK / WEL (Workplace exposure limits, EH40/2005, 2007) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
64-17-5	1000 ppm	-	-	-	-
67-63-0	400 ppm	500 ppm	-	-	-
78-93-3	200 ppm	300 ppm	-	-	-
123-42-2	50 ppm	75 ppm	-	-	-

**Derived no effect level (DNEL) or derived minimum effect level (DMEL):**

DIACETONE ALCOHOL (CAS: 123-42-2)

Final use: Workers.

Exposure method: Dermal contact.

This Safety Data Sheet is prepared in accordance with  
Annex II to Regulation (EC) No 1907/2006

First editing date : 10/09/1997  
Date of last updating : 24/04/2012  
Validation date : 27/03/2014

Potential health effects: Long term systemic effects.

DNEL : 9.4 mg/kg body weight/day

Exposure method: Inhalation.

Potential health effects: Short term local effects.

DNEL : 240 mg of substance/m<sup>3</sup>

Exposure method: Inhalation.

Potential health effects: Long term systemic effects.

DNEL : 66.4 mg of substance/m<sup>3</sup>

Final use: Consumers.

Exposure method: Ingestion.

Potential health effects: Long term systemic effects.

DNEL : 3.4 mg/kg body weight/day

Exposure method: Dermal contact.

Potential health effects: Long term systemic effects.

DNEL : 3.4 mg/kg body weight/day

Exposure method: Inhalation.

Potential health effects: Short term local effects.

DNEL : 120 mg of substance/m<sup>3</sup>

Exposure method: Inhalation.

Potential health effects: Long term local effects.

DNEL : 11.8 mg of substance/m<sup>3</sup>

Exposure method: Inhalation.

Potential health effects: Long term systemic effects.

DNEL : 11.8 mg of substance/m<sup>3</sup>

#### Predicted no effect concentration (PNEC):

DIACETONE ALCOHOL (CAS: 123-42-2)

Environmental compartment: Soil.

PNEC : 0.63 mg/kg

Environmental compartment: Fresh water.

PNEC : 2 mg/l

Environmental compartment: Sea water.

PNEC : 0.2 mg/l

Environmental compartment: Intermittent waste water.

PNEC : 1 mg/l

Environmental compartment: Fresh water sediment.

PNEC : 9.06 mg/kg

Environmental compartment: Marine sediment.

PNEC : 0.91 mg/kg

Environmental compartment: Waste water treatment plant.

PNEC : 82 mg/l

## 8.2. Exposure controls

### Personal protection measures, such as personal protective equipment

Pictogram(s) indicating the obligation of wearing personal protective equipment (PPE) :



Use personal protective equipment that is clean and has been properly maintained.

Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

#### - Eye / face protection

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles with protective sides accordance with standard EN166.

In the event of high danger, protect the face with a face shield.

This Safety Data Sheet is prepared in accordance with  
Annex II to Regulation (EC) No 1907/2006

First editing date : 10/09/1997  
Date of last updating : 24/04/2012  
Validation date : 27/03/2014

Prescription glasses are not considered as protection.

Individuals wearing contact lenses should wear prescription glasses during work where they may be exposed to irritant vapours.

Provide eyewash stations in facilities where the product is handled constantly.

#### - Hand protection

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN374.

Gloves must be selected according to the application and duration of use at the workstation.

Protective gloves need to be selected according to their suitability for the workstation in question : other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.

Type of gloves recommended :

- PVA (Polyvinyl alcohol)

Recommended properties :

- Impervious gloves in accordance with standard EN374

#### - Body protection

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

---

## SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on basic physical and chemical properties

#### General information :

Physical state : Viscous liquid.

#### Important health, safety and environmental information

pH : Not stated.

Neutral.

Boiling point/boiling range : > 35°C

Flash Point Interval : PE < 23°C

Vapour pressure (50°C) : Below 110 kPa (1.10 bar).

Density : < 1

Water solubility : Insoluble.

Viscosity:  $\nu < 7 \text{ mm}^2/\text{s}$  (40°C)

Melting point/melting range : -112 °C.

Self-ignition temperature : 371 °C.

Decomposition point/decomposition range : Not specified.

### 9.2. Other information

---

## SECTION 10 : STABILITY AND REACTIVITY

### 10.1. Reactivity

No data available.

### 10.2. Chemical stability

This mixture is stable under the recommended handling and storage conditions in section 7.

### 10.3. Possibility of hazardous reactions

When exposed to high temperatures, the mixture can release hazardous decomposition products, such as carbon monoxide and dioxide, fumes and nitrogen oxide.

### 10.4. Conditions to avoid

Any apparatus likely to produce a flame or to have a metallic surface at high temperature (burners, electric arcs, furnaces etc.) must not be allowed on the premises.

Avoid :

- accumulation of electrostatic charges.
- heating
- heat
- flames and hot surfaces

### 10.5. Incompatible materials

### 10.6. Hazardous decomposition products

The thermal decomposition may release/form :

- carbon monoxide (CO)

This Safety Data Sheet is prepared in accordance with  
Annex II to Regulation (EC) No 1907/2006

First editing date : 10/09/1997  
Date of last updating : 24/04/2012  
Validation date : 27/03/2014

- carbon dioxide (CO<sub>2</sub>)

---

## SECTION 11 : TOXICOLOGICAL INFORMATION

### 11.1. Information on toxicological effects

Exposure to vapours from solvents in the mixture in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system.

Symptoms produced will include headaches, numbness, dizziness, fatigue, muscular asthenia and, in extreme cases, loss of consciousness.

Repeated or prolonged contact with the mixture may cause removal of natural oil from the skin resulting in non-allergic contact dermatitis and absorption through the skin.

May have reversible effects on the eyes, such as eye irritation which is totally reversible by the end of observation at 21 days.

Splashes in the eyes may cause irritation and reversible damage

#### 11.1.1. Substances

##### Acute toxicity :

DIACETONE ALCOHOL (CAS: 123-42-2)

Oral route : LD<sub>50</sub> = 3002 mg/kg

Species : Rat

OECD Guideline 401 (Acute Oral Toxicity)

Dermal route : LD<sub>50</sub> = 13630 mg/kg

Species : Rabbit

Inhalation route : LC<sub>50</sub> = 7.6 mg/l

OECD Guideline 403 (Acute Inhalation Toxicity)

#### 11.1.2. Mixture

No toxicological data available for the mixture.

##### Monograph(s) from the IARC (International Agency for Research on Cancer) :

CAS 64-17-5 : IARC Group 1 : The agent is carcinogenic to humans.

CAS 67-63-0 : IARC Group 3 : The agent is not classifiable as to its carcinogenicity to humans.

---

## SECTION 12 : ECOLOGICAL INFORMATION

### 12.1. Toxicity

#### 12.1.1. Substances

DIACETONE ALCOHOL (CAS: 123-42-2)

Fish toxicity : LC<sub>50</sub> > 100 mg/l

Species : *Oryzias latipes*

Duration of exposure : 96 h

OECD Guideline 203 (Fish, Acute Toxicity Test)

Crustacean toxicity : EC<sub>50</sub> > 1000 mg/l

Species : *Daphnia magna*

Duration of exposure : 48 h

OECD Guideline 202 (*Daphnia* sp. Acute Immobilisation Test)

Algae toxicity : EC<sub>50</sub> > 1000 mg/l

Species : *Pseudokirchnerella subcapitata*

Duration of exposure : 72 h

OECD Guideline 201 (Alga, Growth Inhibition Test)

#### 12.1.2. Mixtures

No aquatic toxicity data available for the mixture.

### 12.2. Persistence and degradability

#### 12.2.1. Substances

DIACETONE ALCOHOL (CAS: 123-42-2)

Biodegradability : no degradability data is available, the substance is considered as not degrading quickly.

### 12.3. Bioaccumulative potential

No data available.

### 12.4. Mobility in soil

No data available.

This Safety Data Sheet is prepared in accordance with  
Annex II to Regulation (EC) No 1907/2006

First editing date : 10/09/1997  
Date of last updating : 24/04/2012  
Validation date : 27/03/2014

**12.5. Results of PBT and vPvB assessment**

No data available.

**12.6. Other adverse effects**

No data available.

---

**SECTION 13 : DISPOSAL CONSIDERATIONS**

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

**13.1. Waste treatment methods**

Do not pour into drains or waterways.

**Waste :**

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

**Soiled packaging :**

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

---

**SECTION 14 : TRANSPORT INFORMATION**

Transport product in compliance with provisions of the ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport (ADR 2013 - IMDG 2012 - ICAO/IATA 2014).

**14.1. UN number**

1263

**14.2. UN proper shipping name**

UN1263=PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning and reducing compound)

**14.3. Transport hazard class(es)**

- Classification :

3

**14.4. Packing group**

III

**14.5. Environmental hazards**

-

**14.6. Special precautions for user**

ADR/RID	Class	Code	Pack gr.	Label	Ident.	LQ	Provis.	EQ	Cat.	Tunnel
	3	F1	III	3	33	5 L	163 650 640H	E1	3	D/E
IMDG	Class	2°Label	Pack gr.	LQ	EMS	Provis.	EQ			
	3	-	III	5 L	F-E, S-E	163 223 955	E1			
IATA	Class	2°Label	Pack gr.	Passager	Passager	Cargo	Cargo	note	EQ	
	3	-	III	355	60 L	366	220 L	A3 A72	E1	
	3	-	III	Y344	10 L	-	-	A3 A72	E1	

For limited quantities, see part 2.7 of the OACI/IATA and chapter 3.4 of the ADR and IMDG.

For excepted quantities, see part 2.6 of the OACI/IATA and chapter 3.5 of the ADR and IMDG.

**14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**

No data available.

---

**SECTION 15 : REGULATORY INFORMATION****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****- Classification and labelling information included in section 2:**

The following regulations have been used:

- Directive 67/548/EEC and its adaptations

- Directive 1999/45/EC and its adaptations

- Regulation EC 1272/2008 modified by regulation EC 618/2012

- EU Regulation No. 1272/2008 amended by EU Regulation No. 758/2013.

This Safety Data Sheet is prepared in accordance with  
Annex II to Regulation (EC) No 1907/2006First editing date : 10/09/1997  
Date of last updating : 24/04/2012  
Validation date : 27/03/2014



- Container information:

No data available.

- Particular provisions :

No data available.

15.2. Chemical safety assessment

No data available.

---

## SECTION 16 : OTHER INFORMATION

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

In compliance with directives 67/548/EEC, 1999/45/EC and their amendments.

Hazard symbols :

Irritant            Highly flammable

Risk phrase :

R 36            Irritating to eyes.

R 11            Highly flammable.

Safety phrase :

S 16            Keep away from sources of ignition - No smoking.

S 26            In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S 60            This material and its container must be disposed of as hazardous waste.

S 9            Keep container in a well-ventilated place.

Title for H, EUH and R indications mentioned in section 3 :

H225            Highly flammable liquid and vapour.

H226            Flammable liquid and vapour.

H319            Causes serious eye irritation.

H335            May cause respiratory irritation.

H336            May cause drowsiness or dizziness.

EUH066        Repeated exposure may cause skin dryness or cracking.

R 11            Highly flammable.

R 36            Irritating to eyes.

R 36/37        Irritating to eyes and respiratory system.

R 66            Repeated exposure may cause skin dryness or cracking.

R 67            Vapours may cause drowsiness and dizziness.

Abbreviations :

DNEL : Derived No-Effect Level

PNEC : Predicted No-Effect Concentration

ADR : European agreement concerning the international carriage of dangerous goods by Road.

IMDG : International Maritime Dangerous Goods.

IATA : International Air Transport Association.

ICAO : International Civil Aviation Organisation

RID : Regulations concerning the International carriage of Dangerous goods by rail.

GHS02 : Flame

GHS07 : Exclamation mark

This Safety Data Sheet is prepared in accordance with  
Annex II to Regulation (EC) No 1907/2006

First editing date : 10/09/1997  
Date of last updating : 24/04/2012  
Validation date : 27/03/2014