

Exterior Wood Primer is a water-based primer for priming surfaces such as façades, windows, fences and carports. The product protects the wood, as well as enhancing adhesion and durability of a subsequent surface treatment. Exterior Wood Primer is very well suited for fir, accoya, larch, pine, oak and pressure-impregnated wood.

- **Reduces cracking in the wood**
- **Extends the lifetime of the wood**
- **Protects the wood against moisture**



Application area

For new and old wood. Very well suited for fir, accoya, larch, pine, oak and pressure impregnated wood.

Work description

Preparation	Clean the surface with WOCA Exterior Wood Cleaner. The surface must be completely dry and free of dust, dirt and algae. New wood should be treated as soon as possible. On previously-treated wooden surfaces, remove old loose paint and oil. Always remember to test on a less visible spot to check the compatibility of the surface with the product.
Treatment	Shake the container well. Apply Exterior Wood Primer undiluted, with a brush or roller. It is important that the product is applied thoroughly and evenly. Start with the end sections of the wood. The treatment must be performed in dry weather, at a temperature between 15-30° C. Avoid direct sunlight and intense heat. Wood humidity must not exceed 17%. Leave the wood to dry for at least 24 hours before treatment.
Note	Exterior Wood Primer is a pre-treatment product, so the surface must then be treated with WOCA Exterior Wood Oil or paint within 14 days. Make sure that you have properly sealed the container after use. Check the treated surfaces annually. Repair any damage immediately. Optimum durability is achieved by regular cleaning and correct treatment, depending on the construction, the condition of the wood and wind and weather.

Drying time

Fully hard	24 hours
------------	----------



Exterior Wood Primer

**Water-based primer for highly absorbent
wood**

Technical Data Sheet

03.09.2019 – p. 2/2

Technical data

Binder	Alkyd dispersion
Density	1.00 g/ml
Solid content	Approx. 10 %
Shelf life	3 years
Application Temperature	+ 15-30° C
Coverage	10-15 m ² /L, depending on wood variety
Mixing ratio	Use undiluted
Cleaning of tools	Clean in warm water
Storage	+ 10-30°. Keep out of reach of children. Must not be exposed to heat [e.g. sunlight]. Store frost-free.
VOC	This product contains max. 15 g VOC/l. The permitted value is 30 g VOC/l [cat.A/g].
Packaging	2.5 L

Maintenance and related products

Deep cleaning	Exterior Wood Cleaner, #617925
Related products	Exterior Wood Oil, #6179XX
Accessories	Long angled brush 70mm, #599600 Patio scrubber, #599601 Telescopic rod, #599651 Paint roller rod, #599650 Paint roller, #88004

Contact

WOCA Denmark A/S
Tværvej 6
DK - 6640 Lunderskov
T +45 9958 5600
info@wocadenmark.com
wocadenmark.com

This information is based on extensive laboratory testing and practical experience. Because the conditions under which the product is used are often beyond the control of WOCA Denmark, we can only guarantee the quality of the actual product. WOCA Denmark A/S accepts no liability for incorrect use and handling of the product. In principle, this product can be considered an intermediate product, as results depend on construction, the nature of the surface, pre-treatment, temperature, air humidity, application etc. WOCA Denmark A/S reserves the right to change the product and the stated information without notice. This label/product description replaces all previous versions.