



General Description

Junckers RUSTIC TOP OIL is used for refreshing and regular maintenance of oil treated wooden floors:

Spot repair of new floors with minor scratches from installation.
Regular maintenance of the floor.

Junckers RUSTIC TOP OIL is a fast drying maintenance oil giving a ready-for-use surface after approx. 30 minutes.

For maintenance of worn and grey oiled surfaces use **Junckers RUSTIC OIL** or **Junckers SOLID 100 OIL** for priming before **Junckers RUSTIC TOP OIL** is applied.

Technical Data

Product:	Water based aqueous alkyd oil.
Package sizes:	2.5 litre, 5 litre and 10 litre.
Appearance:	Dries to silk matt.
Coverage:	30-50 m ² per litre.
Application tools:	A cotton cloth, or a floor mop or a polishing machine with nylon pad.
Surface temperature:	Minimum 10°C.
Dilution:	Delivered ready for use. Dilution is not recommended.
Drying time:	Dry to touch for light traffic after approx. 30-60 minutes at 20°C. Full wearing strength is achieved after 24 hours.
Cleaning of tools:	Tools should be cleaned with clean water immediately after use.
Storage:	Lasts for 2 years if unopened and stored at 20°C. Not to be exposed to temperatures below 0°C.

System Recommendations

All areas: 1 x **Junckers RUSTIC TOP OIL**
+ 30-60 minutes drying time
+ 1 x **Junckers RUSTIC TOP OIL**.

The frequency of treatment with **Junckers RUSTIC TOP OIL** varies with the amount of traffic on the floor. The more traffic the higher the frequency of the treatment.

Directions for Use

Oiled surfaces must be absolutely clean, dry and free from dust, grease, polish and detergent residue. Irregularities, dirt and blotches can be removed by lightly sanding with fine-grained sandpaper, 180-240 grit, or a polishing machine equipped with a corresponding pad. Remove sanding dust with a vacuum cleaner.

Smaller surfaces such as tabletops: Pour a little **Junckers RUSTIC TOP OIL** onto a dry, cotton cloth and apply it in an even thin layer.

Larger surfaces, such as floors: Pour a little oil onto a floor cloth and apply it evenly, without overlapping too much, doing a small area at a time with the help of a scrubbing brush or a polishing machine fitted with a cloth pad.

Junckers RUSTIC TOP OIL rapidly sets and should therefore not be worked in too long in the same place keeping any overlaps with dry areas to a minimum. If there are any blotches after treatment, polish when dry with a green scrubbing sponge or, on more extensive surfaces, with a scrubbing pad floor cloth, or a polishing machine equipped with a polishing disk. The oil treated surface will be more resistant to dirt after polishing.

Spot repairs:

Floors regularly maintained with **Junckers RUSTIC TOP OIL** can be spot repaired in walking lanes and other areas with high traffic.

Please note!

It is important to ensure that the priming oil is intact and is one of Junckers oils before you apply **Junckers RUSTIC TOP Oil**. If this is not the case the surface must first be sanded and primed with **Junckers RUSTIC OIL** or **Junckers RUSTIC SOLID 100 OIL**.

Important!

Before use of the product, read the label on the container carefully and observe the advised precautionary safety measures.

Important!

Stir well before use.

Further information

Products:

F 2.1 - **Junckers RUSTIC OIL**
F 2.4 - **Junckers RUSTIC SOLID 100 OIL**