



Safety data sheet

267 Worktop Oil

1. Identification of the substance/preparation and of the company/undertaking

Prepared on: 08-10-2010/ LFH
Replaces: 20-10-2009

Product use: Oil treatment of wood

Distributor:

WoodCare Denmark A/S
Tværvvej 6
6640 Lunderskov

Tel:99585600 Fax:99585634

Emergency telephone number: 99585600

The emergency telephone is open between 8 a.m. and 4 p.m. on workdays.

Contact person:Environment Directorate

Email: info@ttwoodcare

2. Hazards identification

DSD/DPD-classification

The product shall not be classified as hazardous according to the national classification and labelling rules.

Additional information

Risk of self-ignition: Due to the risk of self- ignition it is important that sanding dust and oil wetted cloths are soaked in water and disposed of in a tightly closed container after use

3. Composition/information on ingredients

| Einecs no. | CAS No. | Substances | DSD-Classification | w/w% |
|------------|------------|----------------------|--------------------|---------|
| 258-901-1 | 53988-05-9 | Calcium isononanoate | Xi; R36/38 | 1-3 - |
| 265-149-8 | 64742-47-8 | isoalkanes | Xn;R65, R66 | 40-50 4 |
| 265-150-3 | 64742-48-9 | hydrocarbon mixtures | Xn;R65,R66 | 1-3 4 |

4) R65 is not applicable due to the high viscosity of the product.

Please see section 16 for the full text of the R-phrases

4. First aid measures

Inhalation

Seek fresh air.

Ingestion

Wash out mouth thoroughly and drink 1-2 glasses of water in small sips. Seek medical advice if symptoms persist.

Skin

Wash the skin thoroughly with water and continue washing for a long time.

Eyes

Rinse immediately with water (preferably using eye wash) for at least 5 minutes. Open eyes wide. Remove any contact lenses.

Other information

When obtaining medical advice, show the safety data sheet or label. Symptoms: See section 11.

5. Fire-fighting measures

Extinguish with powder, foam, carbon dioxide or water mist. Do not use water stream, as it may spread the fire. Use water or water mist to cool non-ignited stock. Move containers from danger area if it can be done without risk. Avoid inhalation of vapour and flue gases – seek fresh air.

Prepared on: 08-10-2010/LFH
Replaces: 20-10-2009

267 Worktop Oil

6. Accidental release measures

Prevent spillage from entering drains and/or surface water.

7. Handling and storage

Handling

See section 8 for information about precautions for use and personal protective equipment. Smoking and naked flames prohibited.

Storage

Store safely, out of reach of children and not together with food, animal feeding stuffs, medicines, etc. Do not expose to heat (e.g. sunlight). Store frost-free. Keep in tightly closed original packaging.

8. Exposure controls/ personal protection

Precautions for use

Use the product under well-ventilated conditions.

Respiratory protection

Not required.

Gloves and protective clothing

Wear protective gloves made of nitrile rubber,

Eye protection

Wear safety goggles if there is a risk of eye splash.

Occupational exposure limits

Contains no substances subject to reporting requirements.

9. Physical and chemical properties

State: Liquid

Flash point: -°C >100

Density: - g/ml 0,88

10. Stability and reactivity

The product is stable when used in accordance with the supplier's directions.

11. Toxicological information

Acute

Inhalation

Inhalation of vapours may cause irritation to the upper airways.

Ingestion

Harmful if swallowed.

Skin contact

Irritating to skin – may cause reddening.

Eye contact

May cause eye irritation.

Long-term effects

None known.

Prepared on: 08-10-2010/LFH
Replaces: 20-10-2009

267 Worktop Oil

12. Ecological information

Avoid discharge to drain or surface water.

13. Disposal considerations

Not considered as special waste according to Commission decision as regards the list of wastes 2001/118/EC. Contact the local authorities.

14. Transport information

The product is not covered by the rules for transport of dangerous goods by road and sea according to ADR and IMDG.

15. Regulatory information

Hazard designation: It has been assessed that the product shall not be classified as hazardous according to the national classification and labelling rules.

Other labelling

Risk of self-ignition: Due to the risk of self- ignition it is important that sanding dust and oil wetted cloths are soaked in water and disposed of in a tightly closed container after use

Volatile organic compounds (VOC):

This product contains a maximum of 45 g VOC/L. The limit value is 500 g VOC/L (cat. A/i)

Chemical safety assessment

Chemical safety assessment has not been performed.

16. Other information

Restrictions on use

Training requirement

No special training is required, but a thorough knowledge of this safety data sheet should be a prerequisite condition.

Sources used

Other information

This safety data sheet was prepared from information provided by the supplier about physical/chemical properties and all ingredients in the product.

Full text of the R-phrases that are stated in section 3.

R36/38 Irritating to eyes and skin.

R38 Irritating to skin.

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R65 Harmful: May cause lung damage if swallowed.

R66 Repeated exposure may cause skin dryness or cracking.

Amendments have been made in the following sections

7,15