



www.rustins.co.uk

PRODUCT DATA SHEET

Product	Danish Oil
Type	Rustins Danish Oil is a blend of oils (including Tung Oil), resins and driers, formulated to produce an attractive and durable finish. The finish is Satin. For a gloss finish, use Rustin's Teak Oil .
Intended Use	For all interior & exterior bare wood, doors, joinery, garden and indoor furniture.
Special Features	Brings out the natural beauty of wood and veneered surfaces, gives a natural open-grained low lustre finish. Easy to maintain. Conforms to Safety of Toys Regulations BS EN 71 Part 3 1995.
Preparation	The bare wood must be clean, smooth, dry and free from wax, dust and contaminants. Remove wax by scrubbing with white spirit or Rustin's Surface Cleaner and a scouring pad, then wipe away whilst still wet with clean rags. Existing paint and varnishes should be removed with Rustin's Strypit Paint and Varnish Stripper . Bare wood may be dyed before coating with Rustin's Wood Dye . Do not apply Knotting.
Application	Apply liberally with a clean rag or brush and wipe off the surplus oil after a few minutes. On exterior wood, the first coat should be applied liberally with a brush and allowed to dry without wiping. Nibs may be removed from the final coat by applying oil with a scouring pad, rubbing in the direction of the grain, then wiping away the surplus with clean rags or paper kitchen towels.
Coats	Bare wood requires 3 coats. Exterior wood may require extra coats. See below.
Drying Time	4-6 hours depending on temperature and humidity.
Re-coating Time	Re-coat once the previous coat is dry.
Application Temp.	Ideally 15-25°C, do not apply below 5°C or on exterior surfaces if rain is expected.
Coverage	About 14sq.m per litre, 1 coat, depending on the absorbency of the wood.
Maintenance	Periodic re-oiling is required. Clean surfaces before re-oiling using White Spirit.
Compatibility	Danish Oil may be used over the following Rustin's products. Wood Dye, Grainfiller, and Woodstopping . The dye may also be added to Danish Oil. Rustin's Polyurethane Varnish may be applied over Rustin's Danish Oil at any time and the product can also be used as a wood primer before applying undercoat. The surface must be clean before varnishing.
Important Instructions for Exterior Wood	Exterior wood will require re-oiling at least annually; horizontal surfaces and very exposed locations may require more frequent attention. Oak and softwoods are prone to weather staining caused by moisture activating mould spores present naturally in the wood. Extra coats will be required initially to effectively seal these timbers; especially areas of endgrain and up to 6 coats may be appropriate with regular maintenance coats.
Shelf-life/Storage	Many years if stored in original, tightly closed container in normal cool, dry conditions.
Hazards	Flammable. Avoid contact with eyes and skin. Use in a well ventilated area. Keep out of reach of children. Keep away from sources of ignition – no smoking. Keep container tightly closed. A full safety data sheet is available upon request. Important: Rags used for oiling should be laid out flat to dry; otherwise they may catch fire due to spontaneous combustion.
Clean-Up	Clean brushes with White Spirit or Rustin's Brush Cleaner whilst still wet. If dried on, clean brushes with Rustin's Brush Restorer .
Sizes	250ml 500ml 1litre 5litre 25 litre

Rustins Ltd, Waterloo Road, London, NW2 7TX

Tel: 020 8450 4666

Fax: 020 8452 2008

Website address: www.rustins.co.uk

e-mail: rustins@rustins.co.uk