

# A G WOODCARE PRODUCTS LTD

Unit 3, Wellington Road, Waterloo Ind Est, Bidford-on-avon, B50 4JH

Telephone: 01789 778628 / Fax 01789 490296

Email - email@agwoodcare.co.uk

[WWW.AGWOODCARE.CO.UK](http://WWW.AGWOODCARE.CO.UK)

## EXTERIOR HIGH BUILD WOOD OIL

A blend of natural oils & resins offering a transparent satin finish with exceptional durability and resistance for all external joinery & woodwork.

Produces a clear, quick drying, water repellent and weather resistant finish that will not peel or flake when applied following directions below.

Contains UV Filters and is VOC compliant.

To maintain/renovate, re-apply following guidelines below.

## PREPARATION

Ensure all surfaces are clean, dry, and free from any previous finish.

Remove any fungal growth, dirt or moss on old wood prior to application, and ensure a preservative has been applied.

Sand the substrate with a medium 120 grade sanding paper or 120 grade sanding disk, removing all traces of dust.

## APPLICATION

Apply in dry conditions. Always test on a small area prior to initial application. No primer required. Minimum 3 coats recommended. Fiddes Exterior High Build Wood Oil is formulated for application directly, and does not require thinning.

**First Coat** - Stir contents thoroughly before and during use. Apply using a good quality bristle or synthetic brush and apply EVENLY and THOROUGHLY, following the direction of the grain. Leave to dry 4-6 hours in warm, dry well ventilated conditions, or preferably overnight. Sand lightly with fine 320 grade sand paper.

**Second Coat** - Apply as first coat, evenly, allowing good ventilation. Leave to dry 4-6 hours in warm, dry conditions, or preferably overnight.

**Third Coat** - Apply as above. Clean applicators with White Spirit.

## NOTES

Always test on a small area prior to major application.

Ensure timber is dry and has been treated with preservative

Minimum 3 coats recommended

Longer drying periods may occur during application in cold, damp or humid conditions.

Coat all areas thoroughly to seal.

**Re application:** To renovate previous application of Fiddes Exterior High Build Wood Oil, lightly sand area with 150 grit sandpaper and re-apply

**Coverage:** A single application will approximately cover 20-24 square meters per litre, depending on density of substrate.

**Packaging:** 1lt - 2.5lt