

# A G WOODCARE PRODUCTS LTD

Unit 3, Wellington Road, Waterloo Ind Est, Bidford-on-avon, B50 4JH

Telephone: 01789 778628 / Fax 01789 490296

Email - [email@agwoodcare.co.uk](mailto:email@agwoodcare.co.uk)

[WWW.AGWOODCARE.CO.UK](http://WWW.AGWOODCARE.CO.UK)

## FIDDES NGR STAIN 1L / 5L

### Preparation

Sand the wooden substrate in stages, working with a medium Sandpaper (120 grit), through to a medium/ fine grade (180 -220 grit). Always sand in the direction of the grain pattern where possible, ensuring the removal of any blemishes and glue residue prior to the application of Fiddes Wood Dyes. Take care to remove all traces of sanding dust and test the chosen Fiddes Wood Dye on a similar substrate to verify colour / shade.

Stir the contents well and always check the shade before application.

### Application

Take a clean, lint free Cotton Cloth, Brush or Foam Brush and apply in the direction of the wood grain where possible. Take care to remove any excess stain immediately with a separate, clean absorbent cloth, again following the direction of the grain pattern.

To obtain a uniform colour, always wipe evenly, blending the stain over the whole surface area by exerting a degree of pressure when applying by hand. Leave to dry, and do not sand between coats.

The application of additional coats will deepen the existing colour / shade.

Allow to dry fully then apply your chosen top coat, Varnish, Oils, lacquer, Wax polish, Shellac Polish