

March 2017

PRODUCT DATA SHEET

Product	Advanced Wood Protector
Type	Coloured Wood Protector. Available in Medium Brown, Dark Brown, Green and Black.
Intended Use	As a coating for the protection of all types of timber.
Special Features	Finely dispersed ingredients giving better wood penetration and is quick drying. Ready to use – do not dilute.
Preparation	Ensure that timber surfaces are clean and free from previous coatings, grease and contaminants. Surfaces may be damp but the protector should not be applied to decayed wood which should be replaced.
Application	Shake well and stir before use. Apply by brush or coarse spray.
Coats	Apply a minimum of 2 coats.
Drying Time	Between 10 – 15 minutes depending on temperature and humidity.
Re-coating Time	It is important that the second application is applied before the first is dry.
Application Temp.	Ideally 15 – 25°C. Do not apply below 10°C.
Coverage	3 – 4 sq. metres/litre per coat, depending on absorbency of the surface.
Maintenance	Re-apply periodically.
Compatibility	Not compatible with previous coatings, grease and contaminants.
Settlement	Shake well and stir before use or colour obtained will not be correct.
Shelf-life/Storage	Store in a cool dry place with the lid tightly closed. Use within 2 years of manufacture.
Hazards	Very toxic to aquatic organisms. May cause long-term adverse effects in the aquatic environment. Keep out of reach of children. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. After contact with skin, wash immediately with plenty of water. Wear protective clothing, gloves and eye/face protection. A full Safety Data Sheet is available on request and on Rustins Web Site.
Clean-Up	Clean equipment with water.
Sizes	5 Litres