

# WOCA Worktop Kit

For the basic finishing and preservation of solid wood worktops



# WOCA Worktop Kit

For the basic finishing and preservation of solid wood worktops



1



2



## How to do...

- 1 When treating your unfinished/sanded worktop for the first time follow the procedure stated, for pre-oiled worktops only additional maintenance oiling is required so please refer to maintenance section. If the surface of the untreated or sanded wood is particularly smooth, sand the surface with sandpaper grit 120. Make sure the wood is dry and devoid of any dirt or grease. Clean the wood with Wood Cleaner. After cleaning, let the worktop dry and cure within the wood for at least 8 hours.
- 2 Stir the oil thoroughly before use. Use a paintbrush or short haired roller to apply a suitable amount of oil in an even, adequate coat. Wait approx. 20-30 minutes at approx. 20°C as the oil penetrates into the wood. If necessary, sand the wood while the surface is still wet with oil. Sand wet lengthwise along the wood grain with sandpaper grit 320-400. Next, wipe off all excess oil using a lint-free cotton cloth so the surface is dry. Do not leave any excess oil on the surface. Polish the wood carefully using a white polishing pad, which ensures a harder wearing surface. Repeat the treatment on highly absorbent surfaces. The oil is thoroughly hardened after 24/48 hours at ambient 20°C. Do not let the tabletop become wet during the hardening process.

**WOCA Worktop Oil is a unique water resistant – strong oil and is VOC free. The Natural WOCA Worktop oil is suitable for both light and dark types of wood when it has already been pre oiled in the factory.**

WOCA Worktop Oil is a penetrating – oxidizing oil drying to a hard durable and water resistant seal. It adds warmth and depth to all woods and does not leave a surface film to scratch or chip. The product conforms to *The Articles in Contact with Food Regulations* and is therefore suitable for use in contact with food.

### **Please notice!**

**Risk of self-ignition: Due to the risk of self-ignition it is important that oil wetted cloths are soaked in water and disposed of in a tightly closed container after use.**



### **The Box contains**

0.75 litre Worktop Oil  
250 ml Wood Cleaner  
2 Polishing pads  
1 glove  
1 cloth

### **Maintenance**

Use WOCA Worktop Oil or WOCA Worktop Gel to maintain the worktop, every month for the first year, thereafter 4 times a year or as often as necessary. Before starting the maintenance procedure, clean the worktop using Wood Cleaner, and let the surface dry for at least 8 hours. Use a cloth to apply the oil to the surface, leave 20-30 minutes for the oil to penetrate into the wood. Wipe off all excess oil using a lint-free cotton cloth so the surface is dry. Polish the surface carefully using the white polishing pad to remove any standing wood fibers to ensure a hard wearing surface.

### **Coverage**

0,75 Litre covers approximately 9-11 square meters per coat depending on the absorbency of the wood.

### **Storage**

Store in a cool dry place with lid tightly closed, Protect from Frost.

### **Health and safety**

Keep out of the reach of children. In case of contact with eyes rinse immediately with plenty of water and seek medical advice. After contact with skin wash immediately with plenty of water. Wear gloves provided.

699975VO-0