

Special wood floor mastic

Excellent adhesion



Silicone free



Odourless



Special interior



Clean with water



Parquet Joint



PRODUCT DESCRIPTION

- Blanchon **Parquet Joint** is an acrylic mastic designed for joints in wooden floors and wood, laminated and melamine floors, filling cracks, fissures and joints between wooden floors and skirting boards.
- Silicone free, **Parquet Joint** may be lacquered or painted after full polymerization.
- Odourless.
- Maximum expansion: 15%.
- Water resistant after drying.
- Only suitable for interior applications: do not use for "boat deck" joints or for filling between planks on traditional parquet and wooden floors.
- Available in 6 colours: white, oak, beech, medium oak, dark oak, red wood.

SURFACE PREPARATION

- The wood should be sound, clean, dry, free of any traces of existing varnishes, mastics, paints, oils and greases or resins (sand down or strip as necessary with Blanchon Chrono™ Paint Stripper or Blanchon Building Paint Stripper).
- Degrease exotic or resinous wood, if necessary, with an appropriate thinner or acetone. Contaminated wood should be scraped, cleaned and treated with Blanchon Trait'Plus® MU.
- Previously lacquered wooden floors and skirting boards should be clean, dry and free of any traces of adhesive or other coatings that could affect the adhesion of **Parquet Joint** on the substrate.
- Carefully remove all traces of dust.

DIRECTIONS FOR USE

- Ready to use.
- Apply at a temperature between 12°C and 30°C and relative humidity below 85% in accordance with the Standards in force (please contact our Export Department for further information on French building rules and specifications). Only use in well ventilated areas. Do not leave plants and aquariums in areas where the product has been applied.
- Maximum gap width: 20 mm. Maximum depth: 5 mm.
- For best results, it is recommended to "push" **Parquet Joint** rather than "pulling" it.

Cleaning of tools

- Clean tools immediately after use with water. Do not empty into drains.

DRYING TIMES

- Touch dry: around 20 minutes.
- Before recoating: 24 hours minimum.

STORAGE

- Store in the original unopened container in a cool, dry place (once open, use quickly and carefully seal the container after use).
- Protect from frost (be careful of storing in vehicles).

Blanchon

Parquet Joint

TECHNICAL DATA

USE	Mastic for cracks, fissures and joints between parquet and skirting boards
RESIN TYPES	Acrylics
AFNOR CLASSIFICATION	Family IV, class 3
REGULATORY INFORMATION	Refer to the relevant Safety Data Sheet (also available on www.blanchon.com or www.quickfds.com)
TYPE OF PRODUCT	Single component product
TEXTURE	Mastic
TOUCH DRYING	Around 20 minutes at 20°C
BEFORE RECOATING	Minimum 24 hours, under normal conditions of use

Technical Data Sheet issued on the 10.05.2012.

The information provided in this Technical Data Sheet is given in good faith for information purposes only. In no case whatsoever can this information be considered as a guarantee given by us nor engage our responsibility when our products are used. Since we are constantly striving to improve our products, the information given here may be subject to modification without prior notice. This Technical Data Sheet cancels and supersedes all previous versions.

Respect
for people and
the environment



www.blanchon.com

28 rue Charles Martin - BP 105
69192 SAINT-FONS CEDEX - FRANCE
Tél. 04 72 89 06 00 - Fax 04 78 70 07 18
Export Lines: Tel: (0033) 472 89 06 09
Fax: (0033) 472 89 06 02

Blanchon

BLANCHON S.A. - Est. 1832 - A stock company with a board of directors and a supervisory board, with a registered capital of € 4 258 258
390 112 886 RCS LYON - APE 2030 Z - E-mail: info.uk@blanchon.com
Internet : www.blanchon.com